

**Ergonomically styled small size stroboscope with one hand operation and maximum performance**

**Art.No.:3118**

Very compact, ergonomically styled, processor-controlled ministroboscope with analogue dial and external powerpack operation. (powerpack 2020.03 optional)

**Features:**

Small dimensions, low weight, innovative and elegant design, trouble-free processor-technology, very precise adjustment of the flash frequency by rotary knob scale, stabilized voltage, temperature constant.

**General Data:**

Light Source:	flash bulb, internal
Flash bulb:	socket-mounted Xenon-longlife
Light intensity:	max. 450 Lux in 50cm distance from reflector (beam axis)
Flash duration:	approx. 2 - 7 $\mu$ s
Frequency range:	2,5 - 300Hz = 150 - 18.000 RPM ( $\text{min}^{-1}$ ) subdivided into 2 overlapping ranges 1.) 2,5 - 66,6 Hz = 150 - 4000 RPM ( $\text{min}^{-1}$ ) 2.) 61,6 - 300 Hz = 3700 - 18000 RPM ( $\text{min}^{-1}$ )
Trigger action:	internal oscillator
- Internal control:	by dial potentiometer
Display:	reading in Hz (flashes per sec.) or RPM ( $\text{min}^{-1}$ ) by parallax-free scale setting.
Accuracy:	$\pm 2\%$ of the set value
Flash power control:	by change of frequency range via control push button

**Technical Data:**

Power supply:	12V DC Power consumption: max. 1,7A
Housing:	Ergonomically styled industrial design, shatterproof plastic, VDE-approved
Dimensions:	155 x 95 x 85 mm
Weight:	ca. 0,450 kg

**MOVISTROB® Type 3000 B/A**



**Accessories:**

Accupack Type 2020.03  
Red Filter Type 2000.11  
Protective Spectacles  
incl. case Type 950.01  
Telescopic Tripod Type 950.00  
Carrying Case Type 3000.10  
Spare flash bulbs

**Notice:**

Recommended accessory: Power Pack Type 2020.03

